

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Date of issue: 06/05/2015

Revision date: 24/06/2015

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
 Use of the substance/mixture : Marking.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

LA-CO Industries Europe S.A.S.
 Parc Industriel de la Plaine de l'Ain - Allée des Combes.
 01150.BLYES.France.
 Phone: +33 (0)4 74 46 23 23
 Fax: +33 (0)4 74 46 23 29
 E-mail: info@eu.laco.com
 Web: http://www.markal.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 220115 Minsk	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Totleben Boulevard 1606 SOFIA	+359 2 9154 409
CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59
GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirrberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777
HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavik	+354 543 22 22
IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166
LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Riga	+371 67 04 24 73
LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siltnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giftinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)
SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements

: EUH210 - Safety data sheet available on request
EUH208 - Contains 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)(2786-76-7). May produce an allergic reaction

2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Kaolin	(CAS No) 1332-58-7 (EC no) 310-194-1	10 – 50	Not classified
Talc	(CAS No) 14807-96-6 (EC no) 238-877-9	5 – 30	Not classified
Titanium dioxide	(CAS No) 13463-67-7 (EC no) 236-675-5	0.01 – 25	Not classified
Polyethylene Glycol	(CAS No) 25322-68-3 (EC no) 500-038-2	1 – 10	Not classified
barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate]	(CAS No) 1103-38-4 (EC no) 214-160-6	0 – 5	Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 3, H412

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Iron oxide red	(CAS No) 1309-37-1 (EC no) 215-168-2	0 – 2.4	Aquatic Chronic 2, H411
Aluminum hydroxide	(CAS No) 21645-51-2 (EC no) 244-492-7	0 – 1	Not classified
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS No) 2786-76-7 (EC no) 220-509-3	0 – 1	Skin Sens. 1, H317
Aluminum oxide	(CAS No) 1344-28-1 (EC no) 215-691-6	0 – 1	Not classified
Silicon dioxide (amorphous)	(CAS No) 7631-86-9 (EC no) 231-545-4	0 – 0.1	Not classified

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention.
- First-aid measures after skin contact : Wash with plenty of soap and water.
- First-aid measures after eye contact : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : No significant signs or symptoms indicative of any health hazard are expected to occur.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No particular fire or explosion hazard.
- Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear a self contained breathing apparatus. EN469.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

- Protective equipment : Where excessive dust may result, use approved respiratory protection equipment.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Where excessive dust may result, use approved respiratory protection equipment.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Do not discharge into drains or the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Avoid generating dust. Contain and collect as any solid.
- Methods for cleaning up : Minimize generation of dust. On land, sweep or shovel into suitable containers.

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible products : Strong acids. Strong oxidizers. Strong bases.

Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Marking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Polyethylene Glycol (25322-68-3)		
Austria	MAK (mg/m ³)	1000 mg/m ³ (einatembare Fraktion)
Austria	MAK Short time value (mg/m ³)	4000 mg/m ³ max. 4x15 min./Schicht (einatembare Fraktion)
Denmark	Grænseværdie (langvarig) (mg/m ³)	1000 mg/m ³
Denmark	Grænseværdie (kortvarig) (mg/m ³)	2000 mg/m ³
Denmark	Anmærkninger (DK)	(Polyethylenglycol (PEG) med middelmolvægt på 200-600)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1000 mg/m ³
Germany	TRGS 900 Limitation of exposure peaks (mg/m ³)	8000 mg/m ³
Germany	Remark (TRGS 900)	(einatembare Fraktion)
Slovakia	NPHV (priemerná) (mg/m ³)	1000 mg/m ³
Slovakia	Upozornenie (SK)	krátkodobý: kategória II.
Switzerland	VME (ppm)	1000 ppm
Switzerland	Remark (CH)	(mittlere Molmasse 200–600)
Talc (14807-96-6)		
Austria	Remark (AT)	(alveolengängige Fraktion)
Belgium	Remark (BE)	(sans fibre d'amiante)
Finland	HTP-arvo (8h) (mg/m ³)	2 mg/m ³ (Talkki, rakeinen; hengittävää pöly) 1 mg/m ³ (Talkki, rakeinen; alveolijae) 0.5 mg/m ³ (Talkki, kuitumainen)
Hungary	AK-érték	2 mg/m ³
Hungary	Megjegyzések (HU)	respirable aerosol
Ireland	OEL (8 hours ref) (mg/m ³)	10 mg/m ³ total inhalable dust 0.8 mg/m ³ respirable dust
Lithuania	IPRV (mg/m ³)	2 mg/m ³ (ikvepiamoji frakcija) 1 mg/m ³ (alveolinė frakcija)
Netherlands	Remark (MAC)	respirable aerosol
Sweden	nivågränsvärde (NVG) (mg/m ³)	2 mg/m ³ total dust, 1 1 mg/m ³ respirable dust, 1
United Kingdom	Local name	Talc
United Kingdom	WEL TWA (mg/m ³)	1 mg/m ³
United Kingdom	Remark (WEL)	respirable aerosol
Norway	Grenseverdier (AN) (mg/m ³)	3 mg/m ³ (respirabelt støv) 6 mg/m ³ (totalstøv)
Switzerland	Remark (CH)	(respirable aerosol)
Titanium dioxide (13463-67-7)		
Belgium	Remark (BE)	(dioxyde de)
Denmark	Grænseværdie (kortvarig) (mg/m ³)	12 mg/m ³
France	Note (FR)	inhalable aerosol

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Titanium dioxide (13463-67-7)		
Ireland	OEL (8 hours ref) (mg/m ³)	10 mg/m ³ total inhalable dust 4 mg/m ³ respirable dust
Slovakia	NPHV (priemerná) (mg/m ³)	5 mg/m ³
Spain	VLA-ED (mg/m ³)	10 mg/m ³
Spain	Notes	inhalable aerosol
Sweden	nivågränsvärde (NVG) (mg/m ³)	5 mg/m ³
Sweden	Anmärkning (SE)	total dust, 1
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ inhalable aerosol 4 mg/m ³ respirable aerosol
Switzerland	Remark (CH)	(respirable aerosol)
Kaolin (1332-58-7)		
Belgium	Remark (BE)	(fraction alvéolaire)
Denmark	Grænseværdie (kortvarig) (mg/m ³)	4 mg/m ³
Denmark	Anmærkninger (DK)	respirable aerosol
Finland	Huomautus (FI)	(alveolijae)
France	VME (mg/m ³)	10 mg/m ³
France	Note (FR)	respirable aerosol
Spain	VLA-ED (mg/m ³)	2 mg/m ³
Spain	Notes	d,e
United Kingdom	Remark (WEL)	respirable aerosol
Switzerland	Remark (CH)	(respirable aerosol)
Aluminum oxide (1344-28-1)		
Austria	MAK (mg/m ³)	10 mg/m ³ (gemessen als einatembarer Aerosolanteil) 5 mg/m ³ (alveolengängiger Anteil)
Austria	MAK Short time value (mg/m ³)	20 mg/m ³ (gemessen als einatembarer Aerosolanteil) max. 2x60 min./Schicht 10 mg/m ³ (alveolengängiger Anteil) max. 2x60 min./Schicht
Belgium	Limit value (mg/m ³)	10 mg/m ³
Belgium	Remark (BE)	(oxyde d') (en Al)
Denmark	Grænseværdie (langvarig) (mg/m ³)	5 mg/m ³ (total) 2 mg/m ³ (respirabel)
Denmark	Grænseværdie (kortvarig) (mg/m ³)	10 mg/m ³ (total) 4 mg/m ³ (respirabel)
France	VME (mg/m ³)	10 mg/m ³
France	Note (FR)	(respirable aerosol)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	3 mg/m ³
Germany	Remark (TRGS 900)	(gemessen als alveolengängiger Staubanteil)
Hungary	AK-érték	6 mg/m ³
Hungary	Megjegyzések (HU)	(respirable aerosol)
Ireland	OEL (8 hours ref) (mg/m ³)	10 mg/m ³ (total inhalable dust) 4 mg/m ³ (respirable dust)
Lithuania	IPRV (mg/m ³)	2 mg/m ³
Lithuania	Remark (LT)	(alveolinė frakcija. piūrėk IX skyriaus 3 pastabà.)
Poland	NDS (mg/m ³)	2.5 mg/m ³ (dymy, pyl calkowity) 1.2 mg/m ³ (dymy, pyl respirabilny)
Slovakia	NPHV (priemerná) (mg/m ³)	1.5 mg/m ³ (respirabilná frakcia) 4 mg/m ³ (inhalovateľná frakcia)
Spain	VLA-ED (mg/m ³)	10 mg/m ³
Sweden	nivågränsvärde (NVG) (mg/m ³)	5 mg/m ³ (inhalable aerosol) 2 mg/m ³ (respirable aerosol)
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ (inhalable aerosol) 4 mg/m ³ (respirable aerosol)
Norway	Grenseverdier (AN) (mg/m ³)	10 mg/m ³
Norway	Merknader (NO)	1)

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Aluminum oxide (1344-28-1)		
Switzerland	VME (mg/m ³)	3 mg/m ³
Switzerland	Remark (CH)	(respirable aerosol)
Aluminum hydroxide (21645-51-2)		
Austria	MAK (ppm)	10 ppm (gemessen als einatembare Aerosolanteil) 5 ppm (alveolengängiger Anteil)
Austria	MAK Short time value (ppm)	20 ppm (gemessen als einatembare Aerosolanteil) max. 2x60 min./Schicht 10 ppm (alveolengängiger Anteil) max. 2x60 min./Schicht
Poland	NDS (mg/m ³)	2.5 mg/m ³ dymy, pyl calkowity 1.2 mg/m ³ dymy, pyl respirabilny
Slovakia	NPHV (priemerná) (mg/m ³)	1.5 mg/m ³ (respirabilná frakcia) 4 mg/m ³ (inhalovateľná frakcia)
Switzerland	VME (mg/m ³)	3 mg/m ³
Switzerland	Remark (CH)	(alveolengängige Fraktion)
Iron oxide red (1309-37-1)		
Belgium	Remark (BE)	(trioxyde de; fumées, en Fe)
Denmark	Grænseværdie (kortvarig) (mg/m ³)	7 mg/m ³
Denmark	Anmærkninger (DK)	(Jernoxid, total dust)
Finland	Huomautus (FI)	(Fe)
Hungary	Megjegyzések (HU)	(respirabilis por)
Ireland	OEL (8 hours ref) (mg/m ³)	5 mg/m ³ (Iron oxide, fume as Fe) 10 mg/m ³ (Rouge total inhalable dust) 4 mg/m ³ (Rouge total respirable dust)
Ireland	OEL (15 min ref) (mg/m ³)	10 mg/m ³ (Iron oxide, fume as Fe)
Lithuania	Remark (LT)	(Pliurėk IX skyriaus 3 pastabà.)
Poland	Remark (PL)	(dymy)
Slovakia	NPHV (priemerná) (mg/m ³)	1.5 mg/m ³ (respirabilná frakcia) 4 mg/m ³ (inhalovateľná frakcia)
Spain	Notes	(Óxido de hierro(III) (polvo y humos), como Fe)
Sweden	Anmärkning (SE)	(Järnoxid, respirabelt damm)
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ (Rouge, inhalable fraction) 4 mg/m ³ (Rouge, respirable fraction) 5 mg/m ³ (fume, as Fe)
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³ (fume, as Fe)
Norway	Merknader (NO)	(Jern(III)oksid, beregnet som Fe)
Switzerland	Remark (CH)	(alveolengängiger Staub)
Silicon dioxide (amorphous) (7631-86-9)		
Austria	MAK (mg/m ³)	4 mg/m ³
Austria	Remark (AT)	(einatembare Fraktion)
Finland	HTP-arvo (8h) (mg/m ³)	5 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	4 mg/m ³
Germany	Remark (TRGS 900)	(einatembare Fraktion)
Ireland	OEL (8 hours ref) (mg/m ³)	2.4 mg/m ³ 6 mg/m ³ (total inhalable dust)
Spain	VLA-ED (mg/m ³)	10 mg/m ³
Spain	Notes	(respirable aerosol)
United Kingdom	WEL TWA (mg/m ³)	6 mg/m ³ (inhalable aerosol) 2.4 mg/m ³ (respirable aerosol)
Switzerland	VME (mg/m ³)	4 mg/m ³
Switzerland	Remark (CH)	(einatembare Staub)

8.2. Exposure controls

Appropriate engineering controls

: Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Ensure good ventilation of the work station.

Personal protective equipment

: Avoid all unnecessary exposure.

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Hand protection	: None under normal use.
Eye protection	: No special eye protection equipment recommended under normal conditions of use. In case of dust production: protective goggles. EN 166.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges. EN 12083.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable.
Odour	: wax like.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 60 - 85 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 177 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: > 1 Specific Gravity
Solubility	: insoluble in water.
Log Pow	: < 1
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

LD50 oral rat	> 5000 mg/kg (yellow)
---------------	-----------------------

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Polyethylene Glycol (25322-68-3)	
LD50 oral rat	47000 mg/kg
LD50 dermal rat	> 20000 mg/kg
ATE CLP (oral)	47000.000 mg/kg bodyweight
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 6.82 mg/l/4h
Aluminum oxide (1344-28-1)	
LD50 oral rat	> 15900 mg/kg
LC50 inhalation rat (mg/l)	7.6 mg/l/4h
ATE CLP (vapours)	7.600 mg/l/4h
ATE CLP (dust,mist)	7.600 mg/l/4h
barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate] (1103-38-4)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	4.13 mg/l/4h
ATE CLP (vapours)	4.130 mg/l/4h
ATE CLP (dust,mist)	4.130 mg/l/4h
Iron oxide red (1309-37-1)	
LD50 oral rat	> 10000 mg/kg
Silicon dioxide (amorphous) (7631-86-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 58.8 mg/l/4h
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m ³ 4 h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified.

Titanium dioxide (13463-67-7)	
NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

SECTION 12: Ecological information

12.1. Toxicity

Polyethylene Glycol (25322-68-3)	
LC50 fish 1	> 100 mg/l
LC50 other aquatic organisms 1	1000 mg/l
Kaolin (1332-58-7)	
LC50 fish 1	> 1000 mg/l 96 h
EC50 Daphnia 1	> 1000 mg/l 48 h
Aluminum oxide (1344-28-1)	
EC50 Daphnia 1	> 1470 mg/l
NOEC (acute)	> 50 mg/l
barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate] (1103-38-4)	
LC50 fish 1	50 mg/l 48 h
EC50 Daphnia 1	> 3.8 mg/l 48 h

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Iron oxide red (1309-37-1)	
EC50 Daphnia 1	> 100 mg/l
Silicon dioxide (amorphous) (7631-86-9)	
LC50 fish 1	> 10000 mg/l
EC50 Daphnia 1	> 1000 mg/l
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h

12.2. Persistence and degradability

Kaolin (1332-58-7)	
Persistence and degradability	Not readily biodegradable.
barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesulphonate] (1103-38-4)	
Persistence and degradability	Not readily biodegradable. Product persists.
Silicon dioxide (amorphous) (7631-86-9)	
Persistence and degradability	Product persists.
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d

12.3. Bioaccumulative potential

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green	
Log Pow	< 1
barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesulphonate] (1103-38-4)	
BCF fish 1	1.7 - 1.8 mg/l .3 mg/l conc. in enviro/dose
Log Pow	-0.67 - 1.07
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
BCF fish 1	53 l/kg
Log Pow	1.28

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green	
PBT: not yet assessed	
vPvB: not yet assessed	

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose in a safe manner in accordance with local/national regulations.
Sewage disposal recommendations	: Do not dispose of waste into sewer.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
H code	: H7 - 'Carcinogenic': substances and preparations which, if they are inhaled or ingested or if they penetrate the skin, may induce cancer or increase its incidence.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not considered a dangerous good for transport regulations

14.2. UN proper shipping name

Proper Shipping Name (ADR) :

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Inland waterway transport

Carriage prohibited (ADN) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

15.1.2. National regulations

Germany

Water hazard class (WGK) : 1 - low hazard to waters

WGK remark : Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

according to Regulation (EU) No. 2015/830

Indication of changes:

Original Document.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weight Average
	TSCA: Toxic Substances Control Act

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Data sources : ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H351	Suspected of causing cancer
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH208	Contains . May produce an allergic reaction
EUH210	Safety data sheet available on request
R20	Harmful by inhalation
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
N	Dangerous for the environment
Xn	Harmful

LA-CO EU CLP SDS

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product