

# Stylmark® Tube Marker

LA-CO Industries, Inc.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)  
Date of issue: 10/07/2015  
Revision date: 10/29/2015

Version: 1.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Article  
Product name : Stylmark® Tube Marker  
Synonyms : Stylmark® Tube Marker - Black, Blue, Green, Red, White, Yellow  
RS.2000 Paint Refill Tube - Black, Blue, Gree, Red, White Yellow

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking.

### 1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL. 60007-5746  
Phone: (847) 956-7600  
Fax: (847) 956-9885  
E-mail: customer\_service@laco.com



### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification in accordance with the Globally Harmonized Standard

Not classified

### 2.2. Label elements

#### GHS-US labelling

No labelling applicable

### 2.3. Other hazards

### 2.4. Unknown acute toxicity (GHS US)

1.12 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
1.12 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
1.12 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                           | Product identifier  | % (w/w)  | GHS-US classification                 |
|--------------------------------|---------------------|--|---------------------------------------|
| Butyl acetate                  | (CAS No) 123-86-4   | 30.84 – 48.59 Black<br>30.87 – 48.47 Blue<br>30.87 – 48.66 Green<br>31.09 – 48.97 Red<br>29.57 – 46.47 White<br>30.18 – 47.43 Yellow | Flam. Liq. 3, H226<br>STOT SE 3, H336 |
| Titanium dioxide               | (CAS No) 13463-67-7 | 5.05 – 6.32 White<br>1.21 – 1.51 Yellow  | Carc. 2, H351                         |
| Silicon dioxide (cristobalite) | (CAS No) 14808-60-7 | < 0.97 Black, Green<br>< 0.96 Blue<br>< 0.98 Red<br>< 0.92 White<br>< 0.94 Yellow  | Carc. 1A, H350                        |
| Carbon black                   | (CAS No) 1333-86-4  | 0.62 - < 0.89 Black  | Carc. 2, H351                         |

Full text of H-statements: see section 16

# Stylmark® Tube Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
- First-aid measures after ingestion : Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Inhalation of vapours may cause respiratory irritation.
- Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour. Burning produces irritating, toxic and noxious fumes.
- Explosion hazard : May form flammable/explosive vapour-air mixture.
- Reactivity : No dangerous reactions known.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Large amounts: Wear suitable protective clothing and gloves. Chemical goggles or safety glasses.
- Emergency procedures : Evacuate area.

##### 6.1.2. For emergency responders

- Protective equipment : Large amounts: Wear suitable protective clothing and gloves, Chemical goggles or safety glasses.
- Emergency procedures : Stop leak if safe to do so. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Do not allow minor leaks or spills to accumulate on walking surfaces.
- Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container. Following recovery, flush area with water. Clean surface thoroughly to remove residual contamination.

#### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

# Stylmark® Tube Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

|                               |   |
|-------------------------------|---|
| Precautions for safe handling | : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist. Use only outdoors or in a well-ventilated area. |
| Hygiene measures              | : Always wash your hands immediately after handling this product, and once again before leaving the workplace. Do not eat, drink or smoke when using this product.  |

### 7.2. Conditions for safe storage, including any incompatibilities

|                               |   |
|-------------------------------|---|
| Storage conditions            | : Keep container tightly closed.  |
| Incompatible products         | : Strong acids. Strong bases. Strong oxidizers.   |
| Incompatible materials        | : Heat sources. Direct sunlight.  |
| Heat and ignition sources     | : Keep away from heat, sparks and flame.  |
| Prohibitions on mixed storage | : Incompatible materials.   |
| Storage area                  | : Store in dry, cool, well-ventilated area. Keep out of direct sunlight. Keep out of reach of children. |

### 7.3. Specific end use(s)

Marking.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Stylmark® Tube Marker                       |                                     |  |
|---|-------------------------------------|--|
| ACGIH                                       | Not applicable                      |  |
| OSHA  | Not applicable                      |  |
| Butyl acetate (123-86-4)                    |                                     |  |
| ACGIH                                       | ACGIH TWA (mg/m <sup>3</sup> )      | 713 mg/m <sup>3</sup>  |
| ACGIH                                       | ACGIH TWA (ppm)                     | 150 ppm  |
| ACGIH                                       | ACGIH STEL (mg/m <sup>3</sup> )     | 950 mg/m <sup>3</sup>  |
| ACGIH                                       | ACGIH STEL (ppm)                    | 200 ppm  |
| ACGIH                                       | Remark (ACGIH)                      | Eye & URT irr  |
| OSHA  | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 710 mg/m <sup>3</sup>  |
| OSHA  | OSHA PEL (TWA) (ppm)                | 150 ppm  |
| Canada (Quebec)                             | VECD (mg/m <sup>3</sup> )           | 950 mg/m <sup>3</sup>  |
| Canada (Quebec)                             | VECD (ppm)                          | 200 ppm  |
| Canada (Quebec)                             | VEMP (mg/m <sup>3</sup> )           | 713 mg/m <sup>3</sup>  |
| Canada (Quebec)                             | VEMP (ppm)                          | 150 ppm  |
| Silicon dioxide (cristobalite) (14808-60-7) |                                     |  |
| ACGIH                                       | ACGIH TWA (mg/m <sup>3</sup> )      | 0.025 mg/m <sup>3</sup>  |
| ACGIH                                       | Remark (ACGIH)                      | (respirable dust)  |
| OSHA  | OSHA PEL (TWA) (ppm)                | 250 mppcf  |
| OSHA  | Remark (OSHA)                       | (3) See Table Z-3.   |
| Canada (Quebec)                             | VEMP (mg/m <sup>3</sup> )           | 0.1 mg/m <sup>3</sup>  |
| Canada (Quebec)                             | Notations and remarks               | (la poussière respirable), (C2)  |
| Carbon black (1333-86-4)                    |                                     |  |
| ACGIH                                       | ACGIH TWA (mg/m <sup>3</sup> )      | 3.5 mg/m <sup>3</sup>  |
| ACGIH                                       | Remark (ACGIH)                      | Bronchitis   |
| OSHA  | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 3.5 mg/m <sup>3</sup>  |
| Canada (Quebec)                             | VEMP (mg/m <sup>3</sup> )           | 10 mg/m <sup>3</sup> (Fibres de carbone et de graphite; Poussière totale)<br>5 mg/m <sup>3</sup> (Fibres de carbone et de graphite; Poussière respirable)<br>3.5 mg/m <sup>3</sup> |
| Titanium dioxide (13463-67-7)               |                                     |  |
| ACGIH                                       | ACGIH TWA (mg/m <sup>3</sup> )      | 10 mg/m <sup>3</sup>   |
| OSHA  | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 15 mg/m <sup>3</sup>   |
| Canada (Quebec)                             | VEMP (mg/m <sup>3</sup> )           | 10 mg/m <sup>3</sup>   |
| Canada (Quebec)                             | Notations and remarks               | (la poussière totale), (note1)   |

# Stylmark® Tube Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### 8.2. Exposure controls

|                                  |   |
|----------------------------------|---|
| Appropriate engineering controls | : Ensure good ventilation of the work station.  |
| Hand protection                  | : None under normal use.  |
| Eye protection                   | : None under normal use.  |
| Respiratory protection           | : In case of inadequate ventilation wear respiratory protection. Wear appropriate mask. |
| Consumer exposure controls       | : Keep out of reach of children.  |
| Other information                | : Do not eat, drink or smoke when using this product.                                   |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |   |
|---|---|
| Physical state                              | : Liquid  |
| Appearance                                  | : Solid marker containing liquid colored paint. |
| Colour                                      | : Variable.                                     |
| Odour                                       | : Solvent.                                      |
| Odour threshold                             | : No data available                             |
| pH  | : No data available                             |
| Relative evaporation rate (butyl acetate=1) | : No data available                             |
| Melting point                               | : No data available                             |
| Freezing point                              | : 21 - 55 °C                                    |
| Boiling point                               | : > 35 °C                                       |
| Flash point                                 | : 27.5 °C                                       |
| Auto-ignition temperature                   | : No data available                             |
| Decomposition temperature                   | : No data available                             |
| Flammability (solid, gas)                   | : No data available                             |
| Vapour pressure                             | : < 110 kPa                                     |
| Relative vapour density at 20 °C            | : No data available                             |
| Relative density                            | : No data available                             |
| Solubility                                  | : insoluble in water.                           |
| Log Pow                                     | : No data available                             |
| Log Kow                                     | : No data available                             |
| Viscosity, kinematic                        | : No data available                             |
| Viscosity, dynamic                          | : No data available                             |
| Explosive properties                        | : No data available                             |
| Oxidising properties                        | : No data available                             |
| Explosive limits                            | : No data available                             |

### 9.2. Other information

|             |          |
|-------------|----------|
| VOC content | : ≈ 50 % |
|-------------|----------|

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

### 10.5. Incompatible materials

Strong bases. Strong oxidizers. Strong acids.

### 10.6. Hazardous decomposition products

May release flammable gases. Burning produces irritating, toxic and noxious fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                |                  |
|----------------|------------------|
| Acute toxicity | : Not classified |
|----------------|------------------|

# Stylmark® Tube Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

| <b>Butyl acetate (123-86-4)</b> |                            |
|---------------------------------|----------------------------|
| LD50 oral rat                   | 10760 mg/kg                |
| LD50 dermal rabbit              | > 14112 mg/kg              |
| LC50 inhalation rat (mg/l)      | > 21 mg/l/4h               |
| ATE CLP (oral)                  | 10760.000 mg/kg bodyweight |

| <b>Carbon black (1333-86-4)</b> |                             |
|---------------------------------|-----------------------------|
| LD50 oral rat                   | > 8000 mg/kg                |
| LC50 inhalation rat (mg/l)      | > 4.6 mg/m <sup>3</sup> 4 h |

| <b>Titanium dioxide (13463-67-7)</b> |                |
|--------------------------------------|----------------|
| LD50 oral rat                        | > 5000 mg/kg   |
| LC50 inhalation rat (mg/l)           | > 6.82 mg/l/4h |

**Skin corrosion/irritation** : Not classified  
**Serious eye damage/irritation** : Not classified  
**Respiratory or skin sensitisation** : Not classified  
**Germ cell mutagenicity** : Not classified  
**Carcinogenicity** : Not classified.

| <b>Silicon dioxide (cristobalite) (14808-60-7)</b> |  |
|--|--|
| IARC group   | 1 - Carcinogenic to humans, Inhalation of dust |

| <b>Carbon black (1333-86-4)</b>          |  |
|--|--|
| IARC group                               | 2B - Possibly carcinogenic to humans, Inhalation of dust |
| National Toxicology Program (NTP) Status | Not listed in carcinogenicity class                      |

| <b>Titanium dioxide (13463-67-7)</b>        |   |
|---|---|
| NOAEL (chronic, oral, animal/male, 2 years) | 5 mg/kg bodyweight rat                        |
| IARC group                                  | 2B - Possibly carcinogenic to humans, as dust |

**Reproductive toxicity** : Not classified  
**Specific target organ toxicity (single exposure)** : Not classified.  
**Specific target organ toxicity (repeated exposure)** : Not classified  
**Aspiration hazard** : Not classified

### Potential adverse human health effects and symptoms

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Inhalation of vapours may cause respiratory irritation.  
Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.  
Likely routes of exposure : Inhalation;Skin and eye contact

## SECTION 12: Ecological information

### 12.1 Toxicity

No additional information available

### 12.2. Persistence and degradability

| <b>Carbon black (1333-86-4)</b> |                            |
|---------------------------------|----------------------------|
| Persistence and degradability   | Not readily biodegradable. |

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapours are flammable.  
Ecology - waste materials : Avoid release to the environment.

# Stylmark® Tube Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### SECTION 14: Transport information

In accordance with DOT and TDG

|                                  |  |
|----------------------------------|--|
| Transport document description   | : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III |
| UN-No.(DOT)                      | : UN1263   |
| Proper Shipping Name (DOT)       | : Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base                  |
| Transport hazard class(es) (DOT) | : 3 - Flammable liquid   |
| Packing group (DOT)              | : III - Minor Danger   |

#### ADR

|                                  |                                |
|----------------------------------|--------------------------------|
| Transport document description   | : UN 1263 PAINT, 3, III, (D/E) |
| Proper Shipping Name (ADR)       | : PAINT                        |
| Packing group (ADR)              | : III                          |
| Transport hazard class(es) (ADR) | : 3                            |

#### Transport by sea

|                                   |           |
|-----------------------------------|-----------|
| UN-No. (IMDG)                     | : UN 1263 |
| Proper Shipping Name (IMDG)       | : PAINT   |
| Transport hazard class(es) (IMDG) | : 3       |
| Packing group (IMDG)              | : III     |

#### Air transport

|                                   |           |
|-----------------------------------|-----------|
| UN-No. (IATA)                     | : UN 1263 |
| Proper Shipping Name (IATA)       | : Paint   |
| Transport hazard class(es) (IATA) | : 3       |
| Packing group (IATA)              | : III     |

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Butyl acetate (123-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

|  |         |
|--|---------|
| RQ (Reportable quantity, section 304 of EPA's List of Lists) | 5000 lb |
|--|---------|

##### Silicon dioxide (cristobalite) (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

##### Butyl acetate (123-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### Silicon dioxide (cristobalite) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### EU-Regulations

##### Butyl acetate (123-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### Silicon dioxide (cristobalite) (14808-60-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# Stylmark® Tube Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### Carbon black (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Titanium dioxide (13463-67-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### National regulations

#### Stylmark® Tube Marker

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).  
All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).  
All ingredients are listed in the Toxic Substances Control Act (TSCA).

### 15.3. US State regulations

#### Stylmark® Tube Marker

|                            |   |
|----------------------------|---|
| State or local regulations | The carbon black in this product is bound and is not respirable. California Prop. 65 warnings are not required. |
|----------------------------|---|

### Carbon black (1333-86-4)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
|---|---|---|---|-----------------------------------|
| Yes   | No  | No  | No  |                                   |

### Titanium dioxide (13463-67-7)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
|---|---|---|---|-----------------------------------|
| Yes   | No  | No  | No  |                                   |

### Butyl acetate (123-86-4)

U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - List of Hazardous Substances

### Silicon dioxide (cristobalite) (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

### Carbon black (1333-86-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

### Titanium dioxide (13463-67-7)

U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

Indication of changes : SECTION 15.  
Data sources : ACGIH (American Conference of Government Industrial Hygienists).  
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.  
OSHA 29CFR 1910.1200 Hazard Communication Standard.  
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

# Stylmark® Tube Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)


Abbreviations and acronyms : ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number.  
CLP: Classification, Labelling, Packaging.  
EC50: Environmental Concentration associated with a response by 50% of the test population.  
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).  
LD50: Lethal Dose for 50% of the test population.  
OSHA: Occupational Safety & Health Administration.  
PBT: Persistent, Bioaccumulative, Toxic.  
TWA: Time Weight Average.  
TSCA: Toxic Substances Control Act.

Other information : None.

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



### Full text of H-statements:

|              |  |
|--------------|--|
| Carc. 1A     | Carcinogenicity, Category 1A   |
| Carc. 2      | Carcinogenicity, Category 2  |
| Flam. Liq. 3 | Flammable liquids, Category 3  |
| STOT SE 3    | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H226         | Flammable liquid and vapour  |
| H336         | May cause drowsiness or dizziness                                      |
| H350         | May cause cancer   |
| H351         | Suspected of causing cancer  |

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

### LACO NA GHS SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*