

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : SuperFine Metal Marker - Orange

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking.

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
 1201 Pratt Boulevard
 Elk Grove Village, IL. 60007-5746
 Phone: (847) 956-7600
 Fax: (847) 956-9885
 E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flammable liquids, Category 3 H226
 Skin sensitisation, Category 1 H317
 Carcinogenicity, Category 2 H351
 Specific target organ toxicity — Repeated exposure, Category 2 H373

Full text of H statements : see section 16

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

H226 - Flammable liquid and vapour.
 H317 - May cause an allergic skin reaction.
 H351 - Suspected of causing cancer.
 H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof electrical, lighting, ventilating equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P260 - Do not breathe vapours.
 P272 - Contaminated work clothing must not be allowed out of the workplace
 P280 - Wear Butyl rubber gloves.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P314 - Get medical advice/attention if you feel unwell.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P363 - Wash contaminated clothing before reuse.
 P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry extinguishing powder, Water fog to extinguish.
 P403+P235 - Store in a well-ventilated place. Keep cool.

SuperFine Metal Marker - Orange

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS classification
Xylene	(CAS-No.) 1330-20-7	9.3 - 11	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Ethylbenzene	(CAS-No.) 100-41-4	1 - 2.2	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
4-aminonaphthalene-1,8-dicarboximide	(CAS-No.) 1742-95-6	< 2	Skin Sens. 1, H317
Solvent naphtha (petroleum), light aromatic (benzene <0.1%)	(CAS-No.) 64742-95-6	< 1.5	Flam. Liq. 3, H226 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Call a poison center or a doctor if you feel unwell. If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after skin contact : May cause an allergic skin reaction.
- Chronic symptoms : May cause cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : Flammable vapours heavier than air/can accumulate.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

Protection during firefighting : Wear fire/flame resistant/retardant clothing. Positive pressure self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Do not breathe vapours. Avoid contact with skin, eyes and clothing. Eliminate ignition sources.

SuperFine Metal Marker - Orange

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing and gloves. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose in a safe manner in accordance with local/national regulations.

6.4. Reference to other sections

Section 13: disposal information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapours. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Wear Protective gloves. Butyl rubber gloves. Gloves must be replaced after each use and whenever signs of wear or perforation appear.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible products : Strong oxidizers.
Heat and ignition sources : Keep away from heat, sparks and flame.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SuperFine Metal Marker - Orange		
ACGIH	Not applicable	
OSHA	Not applicable	
Xylene (1330-20-7)		
ACGIH	ACGIH TWA (mg/m ³)	434 mg/m ³
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (mg/m ³)	651 mg/m ³
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Canada (Quebec)	VECD (mg/m ³)	651 mg/m ³
Canada (Quebec)	VECD (ppm)	150 ppm
Canada (Quebec)	VEMP (mg/m ³)	434 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm
Ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (mg/m ³)	434 mg/m ³
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (mg/m ³)	543 mg/m ³
ACGIH	ACGIH STEL (ppm)	125 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³

SuperFine Metal Marker - Orange

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Ethylbenzene (100-41-4)

OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Canada (Quebec)	VECD (mg/m ³)	543 mg/m ³
Canada (Quebec)	VECD (ppm)	125 ppm
Canada (Quebec)	VEMP (mg/m ³)	434 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)

ACGIH	Not applicable
OSHA	Not applicable

4-aminonaphthalene-1,8-dicarboximide (1742-95-6)

ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Butyl rubber gloves.
Eye protection	: Eye protection should only be necessary where liquid could be splashed or sprayed.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: No respiratory protection needed under normal use conditions.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Orange
Odour	: aromatic hydrocarbons
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 136.1
Flash point	: 27.2 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 1
Relative density	: > 1
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content	: 10.3 - 13.2 %
-------------	-----------------

SuperFine Metal Marker - Orange

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

None under normal use.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Dermal

Acute toxicity : Not classified

Xylene (1330-20-7)	
LD50 oral rat	> 3500 mg/kg
ATE US (dermal)	1100 mg/kg bodyweight
ATE US (gases)	4500 ppmv/4h
ATE US (vapours)	11 mg/l/4h
ATE US (dust,mist)	1.5 mg/l/4h

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	17.8 ml/kg
LC50 inhalation rat (ppm)	< 1500 ppm
ATE US (oral)	3500 mg/kg bodyweight
ATE US (dust,mist)	1.5 mg/l/4h

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5610 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

Xylene (1330-20-7)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : Not classified
Symptoms/effects after skin contact : May cause an allergic skin reaction.
Chronic symptoms : May cause cancer.

SuperFine Metal Marker - Orange

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Ethylbenzene (100-41-4)	
LC50 fish 1	5.1 mg/l
EC50 other aquatic organisms 1	7.7 mg/l
NOEC (acute)	3.3 mg/l

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)	
LC50 fish 1	8.2 mg/l
EC50 Daphnia 1	4.5 mg/l
EC50 other aquatic organisms 1	3.7 mg/l
NOEC (acute)	0.5 mg/l

12.2. Persistence and degradability

Ethylbenzene (100-41-4)	
Persistence and degradability	Not established.

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Xylene (1330-20-7)	
BCF fish 1	1.3 mg/l
Bioaccumulative potential	Not expected to bioaccumulate.

Ethylbenzene (100-41-4)	
Bioaccumulative potential	Not established.

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

SuperFine Metal Marker - Orange	
Ecology - soil	No additional information available.

12.5. Other adverse effects

Other information : No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with US-DOT 49-CFR and the HMR / TDG / ADR / IMDG / ICAO / IATA

In accordance with DOT

Transport document description : UN1263 Paint, 3, III
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III - Minor Danger

SuperFine Metal Marker - Orange

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Hazard labels (DOT) : 3 - Flammable liquid



Transportation of Dangerous Goods

Transport document description : UN 1263 Paint, 3, III
UN-No. (TDG) : UN 1263
Proper Shipping Name (Transportation of Dangerous Goods) : Paint
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
Packing group : III - Minor Danger

Transport by sea

UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : PAINT
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L

Air transport

UN-No. (IATA) : 1263
Proper Shipping Name (IATA) : PAINT
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	100 lb
-----------	--------

Ethylbenzene (100-41-4)

Subject to reporting requirements of United States SARA Section 313
Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ	1000 lb
-----------	---------

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Xylene (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

SuperFine Metal Marker - Orange

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

EU-Regulations

Xylene (1330-20-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethylbenzene (100-41-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Xylene (1330-20-7)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on Taiwan National Chemical Inventory
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the Chinese Catalog of Hazardous Chemicals.

Ethylbenzene (100-41-4)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Not listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on Taiwan National Chemical Inventory
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the Chinese Catalog of Hazardous Chemicals.

Solvent naphtha (petroleum), light aromatic (benzene <0.1%) (64742-95-6)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on Taiwan National Chemical Inventory
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)

15.3. US State regulations

Ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	54 µg/day

Xylene (1330-20-7)

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) List

Ethylbenzene (100-41-4)

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Washington - Permissible Exposure Limits - TWAs

SuperFine Metal Marker - Orange

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 16: Other information

Data sources : ACGIH (American Conference of Government Industrial Hygienists).
Chemical Inspection & Regulation Service; accessed at: http://www.cirs-reach.com/Inventory/Global_Chemical_Inventories.html.
Component Supplier SDSs.
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
European Chemicals Agency (ECHA) Registered Substances list.
Internal Company test data.
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.


Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

ACGIH (American Conference of Government Industrial Hygienists)
ATE: Acute Toxicity Estimate
CAS (Chemical Abstracts Service) number
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population
LC50: Median lethal concentration
STEL: Short Term Exposure Limits
TSCA: Toxic Substances Control Act
TWA: Time Weighted Average

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43017
T 614-923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product